







45 Higgins Avenue
 Winnipeg, MB R3B 0A8
 Tel: 204.339.6456
 Fax: 204.334.1800
 www.duxtonwindows.com

NAFS Performance Ratings

Conform to AAMA/WDMA/CSA101/I.S.2/A440-08 & CSA A440S1-09

To determine Canadian Building Code requirements, visit:
www.fenestrationcanada.ca/calculator
Please note, A-B-C ratings are no longer relevant.

SERIES	PRODUCT	CLASS	PG	SIZE TESTED	POSITIVE / NEGATIVE DP	WATER TEST PRESSURE	CDN AIR INFIL / EXFIL	FORCED ENTRY RESISTANCE
FIBERWALL™ SERIES 328								
								
328	Combination, 328 Fixed, 325 Casement	CW	65	61" x 47 1/8"	4800 / 4800 Pa	730 Pa	A3	See Note 2
								
328	Combination, 6 Lite Fixed, FG Reinforced	LC	40	96" x 72"	1920 / 1920 Pa	730 Pa	A3	Grade 10
FIBERWALL™ SERIES 458								
								
458	Combination, 6 Lite Fixed, FG Reinforced	CW LC	35 55	96" x 72"	1680 / 1680 Pa 2880 / 2880 Pa	730 Pa	A3	Grade 10
								
458	Combination, 4 Lite, Steel Reinforced	CW	30	92" x 100"	1440 / 1440 Pa	730 Pa	A3	Grade 10






45 Higgins Avenue
 Winnipeg, MB R3B 0A8
 Tel: 204.339.6456
 Fax: 204.334.1800
 www.duxtonwindows.com

NAFS Performance Ratings

Conform to AAMA/WDMA/CSA101/I.S.2/A440-08 & CSA A440S1-09

To determine Canadian Building Code requirements, visit:
www.fenestrationcanada.ca/calculator
Please note, A-B-C ratings are no longer relevant.

SERIES	PRODUCT	CLASS	PG	SIZE TESTED	POSITIVE / NEGATIVE DP	WATER TEST PRESSURE	CDN AIR INFIL / EXFIL	FORCED ENTRY RESISTANCE
FIBERWALL™ SERIES 458								
								
458	Combination, 9 Lite Fixed, Steel Reinforced	CW LC	30 45	108" x 96"	1440 / 1440 Pa 2160 / 2160 Pa	730 Pa	A3	Grade 10
FIBERWALL™ SERIES 658								
								
658	Combination, 6 Lite Fixed, FG Reinforced	CW	60	96" x 72"	2880 / 2880 Pa	730 Pa	A3	Grade 10
								
658	Combination, 9 Lite Fixed, Steel Reinforced	CW	45	108" x 96"	2160 / 2160 Pa	730 Pa	A3	Grade 10

Notes:

- (1) Standard products are not necessarily manufactured to the ratings shown here. Product must be ordered with these specifications in order to achieve this performance. It is the responsibility of the customer to correctly specify the applicable building code and performance requirements. Actual performance is also size and installation dependent.
- (2) Full NAFS testing not conducted on combined product. See individual product ratings for Forced Entry Resistance.